

Sustainability Datasheet

2K-Derocryl Lack Durapid

Product description

Two-component coating based on an acrylate resin, chemically cured with polyisocyanate (polyurethane). For further product information please refer to the technical datasheet.

Ingredients

organic solvent content	approx. 21 wt.%	(depending on the color tone)
VOC value (mixed)	approx. 287 g/l	(depending on the color tone)
hazardous ingredients (according to CLP regulation)	see Safety Datasheet (chapters 2 and 3)	
CMR substances	not a recipe ingredient	
PBT und vPvB substances	not a recipe ingredient	
Lead, Cadmium, Chromium(VI)	not a recipe ingredient, according to DGNB criterion ENV1.2	
free formaldehyde	not a recipe ingredient, according to VdL regulation 01	
halogenated hydrocarbons	not a recipe ingredient	

Building certification - according to DGNB

Suitability of the product/system for the individual quality levels according to the criteria matrix of the DGNB criterion ENV1.2 "Risks for the local environment", versions 2015 to 2023.

Quality level	1	2	3	4
Row 17 Structural metal components with more than 500 m ² of coated surface in the building. Corrosivity category max. C3 high. (construction and factory)	VOC < 120 g/m ²	VOC < 90 g/m ²	VOC < 60 g/m ²	VOC < 30 g/m ²
2K-Derocryl Lack Durapid Film thickness: 80 µm	fulfilled	fulfilled	fulfilled	not fulfilled
Row 19 Non-structural metal components with more than 10 m ² of coated surface in the building. (construction and factory)	VOC < 300 g/l	VOC < 300 g/l	VOC < 140 g/l water-dilutable	VOC < 140 g/l water-dilutable
2K-Derocryl Lack Durapid Film thickness: 80 µm	fulfilled	fulfilled	not fulfilled	not fulfilled

Alternative for metal components pre-painted at the factory:

Verification of the legal limit values according to 31st BImSchV on the base of current, officially accepted monitoring protocols by the coater (equivalent to quality level 4)

Examinations / Approvals

Decopaint directive
(Directive 2004/42/EC)

fulfills category d type Ib „Metal paints for building structures“
maximum permissible value: 300 g/l
calculated value: 287 g/l

RoHS directive
(Directive 2011/65/EU)

does not contain hazardous substances, in concentrations or applications whose placing on the market is prohibited

Corrosion protection class
(DIN EN ISO 12944-6)

fulfills corrosivity category C3 high
at 120 µm

Biobased product
(DIN EN 16785-1)

contains proportions of carbon from renewable sources
DIN CERTCO Gesellschaft für Konformitätsbewertung mbH,
registry no. DIC-00008, report no. 1-3-31-BAW-22 rev. 1

biobased 
GISCODE

PU35

The general information and descriptions contained in this datasheet are given to the best of our knowledge. Our information and data do not represent a guaranteed property in legal sense. Advice on application technology, whether given verbally, in writing or by means of trials, is given only in general terms, also regarding any property rights of third parties. Our general advice does not release you from your obligation to test the products supplied by us for the intended processes and purposes. This applies in particular if products supplied by us are used together with third party products. The application, use and processing of the products are beyond our control and are therefore exclusively your responsibility. In all other respects, our General Terms and Conditions of Sale and Delivery shall be deemed to have been agreed.

Article group: PD4442

Version: 06-02-2024

Dr. Demuth Derisol Lackfarben
GmbH & Co. KG
Hillerser Straße 8
37154 Northeim, Germany

Tel. +49 (0) 5551 9794-0
Fax +49 (0) 5551 9794-30
Mail: info@dr-demuth.com
www.dr-demuth.com